



CondensSmart Zero-loss Drains

Models | CSED0106N to CSED5650N

For System Flow Rates up to 106 SCFM (180 Nm³/hr) to 5650 SCFM (9600 Nm³/hr)


The smart solution to condensate management is now possible with an automatic and efficient zero-loss drain.

The Walker Filtration CondensSmart Electronic Drain is engineered to remove oil-contaminated condensate from the compressed air production system without allowing air to escape.

Controlled by an advanced processor, the device prevents blockages with a specially engineered series of integrated sensory valves that adjust automatically when condensate is detected at the maximum level.

Available in a wide range of models, the CondensSmart Electronic Drain utilizes smart technology to enhance condensate management by eliminating frequent drain maintenance and compressed air loss.

The energy efficient and economic solution to **ZERO** compressed air loss




User Control

Easily identify the drain's operational status and functions with the user-friendly control panel



Easy Installation

Multi-directional inlet connection easily adapts to any orientation within installed systems



Integrated Filtration

An additional filter at the outlet of the device protects the valve from excessive contaminants

- **Automatic Drainage** In case of overflow, the solenoid valve automatically opens and closes itself to release accumulated liquid
- **Contact Alarm** Red LED light signifies the need to manually attend to the device, preventing expensive maintenance costs and damage to the drainage system
- **Premium Protection** Hard-coated aluminum receiver prevents corrosion due to constant contact with contaminated condensate
- **Comprehensive Range** Six different models engineered to maintain a wide variety of air compressor flow rates for optimal system operation







For further information please visit CompressorShop.com



For further information please call: **+1 855-244-3786**

Technical Specification







Model	Power supply (+/- 10%)	Power Watts	Alarm contact	Working pressure range psig (barg)	Working temperature min/max °F (°C)	Maximum discharge volume fluid oz/hr (l/hr)		Maximum capacity SCFM (Nm ³ /hr)			Inlet	Outlet hose barb diameter (with flow limiter) inches (mm)	Weight	
						Nominal	Maximum	Nominal compressor	Dryer	Filter			lbs	kg
CSED0106N	115 VAC (50/60 Hz)	10	X	2.9 - 232 (0.2 - 16)	34/140 (1/60)	112 (3.3)	338 (10)	106 (180)	212 (360)	1059 (1800)	½ NPT (M)	½ (12)	0.9	0.4
CSED0222CN	115 VAC (50/60 Hz)	10	✓	2.9 - 232 (0.2 - 16)	34/140 (1/60)	112 (3.3)	338 (10)	222 (378)	445 (756)	2225 (3780)	½ NPT (F)	½ (12)	1.1	0.5
CSED0265N	115 VAC (50/60 Hz)	10	✓	2.9 - 232 (0.2 - 16)	34/140 (1/60)	169 (5)	507 (15)	265 (450)	530 (900)	2649 (4500)	2 x ½ NPT (F)	½ (12)	1.3	0.6
CSED0530N	115 VAC (50/60 Hz)	10	✓	2.9 - 232 (0.2 - 16)	34/140 (1/60)	338 (10)	676 (20)	530 (900)	1059 (1800)	5297 (9000)	2 x ½ NPT (F)	½ (12)	1.5	0.7
CSED1059N	115 VAC (50/60 Hz)	10	✓	2.9 - 232 (0.2 - 16)	34/140 (1/60)	676 (20)	1183 (35)	1059 (1800)	2119 (3600)	10594 (18000)	2 x ½ NPT (F)	½ (12)	2.6	1.2
CSED5650N	115 VAC (50/60 Hz)	10	✓	2.9 - 232 (0.2 - 16)	34/140 (1/60)	3043 (90)	5072 (150)	5650 (9600)	11301 (19200)	56503 (96000)	2 x ½ NPT (F)	½ (12)	4.0	1.8



CSED0106N

CSED0222CN (Compact)

CSED0265N



CSED0530N

CSED1059N

CSED5650N

Technical Notes

1. Zero Loss drains should be serviced every 12 months / 8000 hours, whichever comes first, by ordering service kit CSSK1.
2. Electric connection is DIN 43650 B (EN 175301-803) for all models.
3. Protection class is NEMA 4 (IP65), with connector and correctly assembled gasket, for all models.
4. The Alarm contact is NC/NO: 240 VAC max - 1A / 30 VDC max - 1A. Alarm connection is M12 Code A 4 Poles (connector not supplied).
5. For 230 VAC and BSP inlet connections or applicable accessories and spares, please consult your local Walker Filtration sales representative.



Compressor Shop

tel: +1 855-244-3786 | email: sales@CompressorShop.com web: CompressorShop.com