

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

SECTION 1. IDENTIFICATION

Product name	:	Semi Synthetic 46
Product code	:	CS-200823
Manufacturer or supplier's d	eta	ils
Manufacturer/Supplier	:	Compressor Shop 3905 Vincennes Road Indianapolis, IN 46268 US
SDS Request	:	
Customer Service	:	(+1) 855-244-3786
Emergency telephone number Spill Information Health Information	:	877-504-9351 877-242-7400

Recommended use of the chemical and restrictions on use Recommended use : Compressor oil.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)			
Skin sensitisation	:	Category 1	
Long-term (chronic) aquatic hazard	:	Category 3	
GHS label elements			
Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: H317 May cause an allergic skin reaction. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.	
Precautionary statements	:	Prevention:	

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water and soap. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Storage:

No precautionary phrases.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label: Contains alkaryl phosphite

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L).

Hazardous components

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Alkaryl phosphite		26523-78-4	0.1 - 0.9
	 phosphite 		

SECTION 4. FIRST-AID MEASURES

If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version 1.2	Revision Date: 10/27/2020	-	DS Number: 0010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
			rinsing. If persistent irritat	ion occurs, obtain medical attention.
If sv	vallowed	:	0	tment is necessary unless large quantities owever, get medical advice.
and	at important symptoms effects, both acute and ayed	:	may include itchin Oil acne/folliculitis of black pustules	(allergic skin reaction) signs and symptoms ng and/or a rash. s signs and symptoms may include formation and spots on the skin of exposed areas. sult in nausea, vomiting and/or diarrhoea.
Pro	tection of first-aiders	:		ng first aid, ensure that you are wearing the mal protective equipment according to the d surroundings.
mee	cation of any immediate dical attention and special tment needed	:	Treat symptomat	cally.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.	
Environmental precautions		Local authorities should be advised if significant spillages	

Environmental precautions : Local authorities should be advised if significant spillages

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Versi 1.2	ion	Revision Date: 10/27/2020		S Number: 0010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
		s and materials for	:		It. Avoid accidents, clean up immediately.
(containi	ment and cleaning up		or other containm Reclaim liquid dire Soak up residue v	ading by making a barrier with sand, earth ent material. ectly or in an absorbent. vith an absorbent such as clay, sand or other and dispose of properly.
,	Additior	nal advice	:	see Section 8 of t	election of personal protective equipment his Safety Data Sheet. lisposal of spilled material see Section 13 of theet.

SECTION 7. HANDLING AND STORAGE

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Further information on stor- age stability	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
		Store at ambient temperature.
Packaging material	:	Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC.
Container Advice	:	Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print D
1.2	10/27/2020	800010042446	Date of

Print Date: 03/26/2021 Date of last issue: 09/23/2020

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral		TWA (Inhal-	5 mg/m3	ACGIH
		able particu-	-	
		late matter)		

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information:

General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 10/27/2020		DS Number: 0010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
			equipment used to equipment, local of Drain down system nance. Retain drain down subsequent recyco Always observe g washing hands af drinking, and/or su protective equipment	ood personal hygiene measures, such as ter handling the material and before eating, moking. Routinely wash work clothing and tent to remove contaminants. Discard con- g and footwear that cannot be cleaned.
Per	sonal protective equipm	ent		
	spiratory protection	:	No respiratory pro conditions of use. In accordance wit	otection is ordinarily required under normal h good industrial hygiene practices, precau- ken to avoid breathing of material.
	nd protection Remarks	:	gloves approved a suitable chemical gloves Suitability usage, e.g. freque sistance of glove glove suppliers. C Personal hygiene Gloves must only gloves, hands sho cation of a non-pe For continuous co through time of m 480 minutes when short-term/splash recognize that sui may not be availa time maybe accept and replacement a good predictor of dependent on the Glove thickness s	act with the product may occur the use of to relevant standards (e.g. Europe: EN374, from the following materials may provide protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on ency and duration of contact, chemical re- material, dexterity. Always seek advice from Contaminated gloves should be replaced. is a key element of effective hand care. be worn on clean hands. After using buld be washed and dried thoroughly. Appli- erfumed moisturizer is recommended. ontact we recommend gloves with break- ore than 240 minutes with preference for > re suitable gloves can be identified. For protection we recommend the same but itable gloves offering this level of protection ble and in this case a lower breakthrough otable so long as appropriate maintenance regimes are followed. Glove thickness is not of glove resistance to a chemical as it is exact composition of the glove material. should be typically greater than 0.35 mm glove make and model.
Eye	e protection	:	Wear full face shi	eld if splashes are likely to occur.
Ski	n and body protection	:		sistant gloves/gauntlets and boots. Where also wear an apron.
Pro	tective measures	:	Personal protective	ve equipment (PPE) should meet recom-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version 1.2	Revision Date: 10/27/2020	SDS Number: 800010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020	
		mended na	tional standards. Check with PPE suppliers.	
Ther	mal hazards	: Not applica	ble	
Envi	ronmental exposure	controls		
Gene	General advice		Take appropriate measures to fulfill the requirements of rele- vant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being dis- charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.	
SECTION	I 9. PHYSICAL AND C	HEMICAL PROPE	RTIES	
Арре	earance	: liquid		
Colo	ur	: colourless		
Odou	ur Threshold	: Data not a	vailable	
pН		: Not applica	able	

Colour	:	colourless
Odour Threshold	:	Data not available
рН	:	Not applicable
pour point	:	Method: Unspecified Not applicable
Initial boiling point and boiling range	:	> 280 °C / 536 °F estimated value(s)
Flash point	:	240 °C / 464 °F
		Method: ASTM D92 (COC)
Evaporation rate	:	Data not available
Flammability (solid, gas)	:	Data not available
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F)
		estimated value(s)
Relative vapour density	:	> 1 estimated value(s)

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Vers 1.2	sion	Revision Date: 10/27/2020		S Number: 010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
	Relative density		:	0.864 (15 °C / 59	°F)
	Density		:	864 kg/m3 (15.0 Method: ASTM D	
	Solubili Wat	ty(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not available	e
	Partition coefficient: n- octanol/water		:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-ignition temperature		:	> 320 °C / 608 °F	
	Decom	position temperature	:	Data not available	e
	Viscosi Visc	ty :osity, dynamic	:	Data not available	e
	Visc	osity, kinematic	:	46 mm2/s (40.0 °	C / 104.0 °F)
				Method: ASTM D	445
	Explosi	ve properties	:	Not classified	
	Oxidizir	ng properties	:	Data not available	e
	Conduc	ctivity	:	This material is n	ot expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reac- tions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise,
	the data presented is representative of the product as a

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Expected to be a skin sensitizer.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the Internation-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

al Agency for Research on Cancer (IARC).

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	
Product:	
	: Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product: Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

rsion	Revision Date: 10/27/2020		0S Number: 0010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
Basis	Basis for assessment		for this product. Information given and the ecotoxico Unless indicated of tive of the product ponent(s).(LL/EL/	lata have not been determined specifically is based on a knowledge of the components logy of similar products. otherwise, the data presented is representa- as a whole, rather than for individual com- IL50 expressed as the nominal amount of o prepare aqueous test extract).
Ecoto	oxicity			
<u>Produ</u> Toxici ty)	uct: ity to fish (Acute toxici-	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
	ity to daphnia and other ic invertebrates (Acute y)	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
Toxici icity)	ity to algae (Acute tox-	:	Remarks: LL/EL/I Harmful	L50 10-100 mg/l
Toxici icity)	ity to fish (Chronic tox-	:	Remarks: Data no	ot available
	ity to daphnia and other ic invertebrates (Chron- city)	:	Remarks: Data no	ot available
	ity to microorganisms e toxicity)	:	Remarks: Data no	ot available
<u>Comp</u>	oonents:			
	yl phosphite: ctor (Acute aquatic tox-	:	1	
M-Fac toxicit	ctor (Chronic aquatic y)	:	1	
Persi	stence and degradabili	ity		
<u>Produ</u>	uct:			
Biode	gradability	:	Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Versi	ion	Revision Date:		OS Number:	Print Date: 03/26/2021
1.2		10/27/2020	80	0010042446	Date of last issue: 09/23/2020
	Bioaco	cumulative potential			
	Produc	ct:			
	Bioacc	umulation	:	Remarks: Contair cumulate.	as components with the potential to bioac-
	Mobilit	ty in soil			
	Produc	<u>ct:</u>			
	Mobility	4	:		under most environmental conditions. vill adsorb to soil particles and will not be
				Remarks: Floats of	on water.
	Other a	adverse effects			
	Produc	<u>ct:</u>			
	Additio mation	nal ecological infor-	 Does not have ozone depletion potential, photochemica ozone creation potential or global warming potential. Product is a mixture of non-volatile components, which be released to air in any significant quantities under no conditions of use. 		tential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal
				Poorly soluble mix Causes physical f	xture. ouling of aquatic organisms.
					ot cause chronic toxicity to aquatic organ- tions less than 1 mg/l.
SEC	TION 1	3. DISPOSAL CONSI	DEF	ATIONS	
	Dispos	sal methods			
	-	from residues	:	toxicity and physic determine the pro ods in compliance	e if possible. ility of the waste generator to determine the cal properties of the material generated to per waste classification and disposal meth- e with applicable regulations. to the environment, in drains or in water

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version 1.2	Revision Date: 10/27/2020	SDS Number: 800010042446	Print Date: 03/26/2021 Date of last issue: 09/23/2020
Cont	aminated packaging	to a recognized the collector or Disposal should	ordance with prevailing regulations, preferably I collector or contractor. The competence of contractor should be established beforehand. I be in accordance with applicable regional, cal laws and regulations.
	al legislation parks		d be in accordance with applicable regional, cal laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitisation

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil -	64742-70-7
unspecified	
Diphenylamine	122-39-4
distillates (petroleum), hydrotreated light	64742-47-8

California Prop. 65

WARNING: This product can expose you to chemicals including distillates (petroleum), hydrotreated light, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil -	64742-70-7
unspecified	

California Permissible Exposure Limits for Chemical Contaminants

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
--	------------

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EINECS	:	Not established.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 2, 1, 0 tivity)

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020
OSH	IH / TWA A Z-1 / TWA eviations and Acronyms		ghted average ghted average breviations and acronyms used in this docu- ked up in reference literature (e.g. scientific
		Hygienists ADR = European Carriage of Dang AICS = Australia ASTM = America BEL = Biological BTEX = Benzer CAS = Chemica CEFIC = Europea CLP = Classifica COC = Clevelan DIN = Deutsches DMEL = Derived DNEL = Derived DSL = Canada I EC = European EC50 = Effective ECETOC = European EC50 = Effective ECAS = The E Chemical Substa EL50 = Effective ENCS = Japane Inventory EWC = European GHS = Globally Labelling of Che IARC = Internation IC50 = Inhibitory IL50 = Inhibitory IMDG = Internation INV = Chinese O IP346 = Institute determination of KECI = Korea E LC50 = Lethal D LL/EL/IL = Lethal LL50 = Lethal LC MARPOL = Internation NOEC/NOEL = I served Effect Le OE_HPV = Occi	ne, Toluene, Ethylbenzene, Xylenes Abstracts Service an Chemical Industry Council ation Packaging and Labelling d Open-Cup s Institut fur Normung Aminimal Effect Level No Effect Level Domestic Substance List Commission e Concentration fifty opean Center on Ecotoxicology and Toxicolo- an Chemicals Agency European Inventory of Existing Commercial ances a Loading fifty se Existing and New Chemical Substances n Waste Code Harmonised System of Classification and micals onal Agency for Research on Cancer onal Air Transport Association r Concentration fifty Level fifty ional Maritime Dangerous Goods Chemicals Inventory e of Petroleum test method N° 346 for the polycyclic aromatics DMSO-extractables xisting Chemicals Inventory oncentration fifty use fifty per cent. al Loading/Effective Loading/Inhibitory loading pading fifty rnational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Semi Synthetic 46 (CS-200823)

Version	Revision Date:	SDS Number:	Print Date: 03/26/2021
1.2	10/27/2020	800010042446	Date of last issue: 09/23/2020

PICCS = Philippine Inventory of Chemicals and Chemical Substances PNEC = Predicted No Effect Concentration REACH = Registration Evaluation And Authorisation Of Chemicals RID = Regulations Relating to International Carriage of Dangerous Goods by Rail SKIN_DES = Skin Designation STEL = Short term exposure limit TRA = Targeted Risk Assessment TSCA = US Toxic Substances Control Act TWA = Time-Weighted Average vPvB = very Persistent and very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Revision Date	:	10/27/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN